37.2 Ton Standard BullDozer

T-REX238-8

The Revaro T-REX2372 is a powerful 37.2-ton heavy-duty crawler bulldozer built for demanding earthmoving, mining, and large-scale construction operations. Powered by a robust 257 kW engine, it delivers exceptional pushing power, reliable performance, and efficient fuel consumption in tough working environments.With a maximum traction force of 281 kN, a durable undercarriage, and multiple blade options including straight-tilt, angle, U, and semi-U blades with capacities up to 16.2 m³, the T-REX2372 is designed to move large volumes of material efficiently. Its strong frame, advanced cooling system, and comfortable operator station ensure durability, productivity, and dependable performance during continuous heavy-duty operation.



Specs

General Specs	
Dimensions	6535×4150×3515mm
Weight	37200kg
Engine model	QSNT-C345S31 / NTA855-C360S10
Power	257kW / 2000r/min
Fuel consumption	222-28 / 29-38L/H
Ground contact length	3150mm
Ground specific pressure	0.105MPa
Minimum ground clearance	500mm
Gradeability	30°
No. of track shoes (each side)	41
Width of Track shoe	560mm
Track Gauge	2140mm
pitch	228.6mm

Tel: +27 78 457 3557 • Email: Danny.scholtz@revaro.co za • WhatsApp/Cell:
Visit us atMiddelburg Industrial Park, Bethal Road / N4, Vaalbank, Middelburg, 1050

A member of the REVARO® Group of Companies

No of carrier rollers (each side)	2
No. of Track roller (each side)	7
Maximum traction force	281KN
Straight-tilt Blade (Capacity & inclination)	4150×1592mm (10m³ & 1000mm)
Angle Blade (Capacity & inclination)	5000×1142mm (6.2m³ & 500mm)
U Blade (Capacity & inclination)	4440×1740 mm(16.2m³ & 1000mm)
Semi-U-Blade (Capacity & inclination)	4150×1712 mm(11.7m³ & 1000mm)
Blade lift height (Straight, Angle, U, Semi-U)	1560/1703/1560/1560mm
Blade depth (Straight, Angle, U, Semi-U)	560/630/560/560mm
Max Forward Speed - F1, F2, F3	3.6, 6.6, 11.5km/h
Max Reverse Speed - R1, R2, R3	4.4, 7.8, 13.5km/h
Coolant capacity	121L
Fuel tank capacity	640L
Engine oil capacity	47L