## 3 Arm Fieldking Sub-soiler Available with pipe-layer

# FKSS-3




The sub soiler are deep tillage implements specially designed for breaking up hard pan layers and loosening the subsoil allowing better drainage, root growth and mineral osmosis.

- Optional wide range of roller/ crumbler available, which helps in breaking bigger lumps to smaller clods. Also it helps in depth control and steady run of the sub soiler.
- Adjustable depth & width of ploughing available for 2, 3 & 5 arm sub-soiler.
- Optional pipe layer attachment available for 1 arm sub soiler.
- Depth can be adjusted by top links.
- It can plough up to 550 mm deep
- The heavy duty pointed chisel
- Optional crumbler available in 3 & 5 arm sub soiler
- Shear bolt protection available in 5 arm sub soiler

### Specs

| General | |
|---|---|
| Length | 830mm |
| Width | 1520mm |
| Height | 1060-1370mm |
| Tillage Width | 1055-1284mm |
| Tyne to Tyne Distance | 465-576mm |
| Tyne | 150mm |
| No. of Tyne | 3 |
| 3 Point Linkage | Cat - II |
| Working Depth | 550mm |
| Crumbler | 33.7mm x 25mm (T) Round Pipe |
| Crumbler Length | 1530mm |

Tel: +27 78 457 3557 • Email: Danny.scholtz@revaro.co za • WhatsApp/Cell:
Visit us atMiddelburg Industrial Park, Bethal Road / N4, Vaalbank, Middelburg, 1050

A member of the REVARO® Group of Companies

| | |
|---|---|
| Weight Without Crumbler | 280kg |
| Weight With Crumbler | 430kg |
| Tractor Power | 80-95HP |

Tel: +27 78 457 3557 • Email: Danny.scholtz@revaro.co za • WhatsApp/Cell:
Visit us atMiddelburg Industrial Park, Bethal Road / N4, Vaalbank, Middelburg, 1050

A member of the REVARO® Group of Companies